

Delock Lighting LED Panel light 18 W warm white Ø 24 cm

Description

With this LED panel light, which is also suitable for recess mounting, you can stylishly stage your living room or office. The low power consumption of only 18 Watt allows you to save money, and the ultra-thin design of the light offers many possibilities of lighting composition. After switching on the panel immediately reaches its full brightness, whereas the LEDs inside the panel are arranged in a way that the light is emitted uniformly over the entire surface without dazzling.



Item no. 46331

EAN: 4043619463312

Country of origin: CHINA

Package: Retail Box

Specification

- Operating voltage: 100-240 V AC 50/60 Hz 0,24 A
- LED Type: 180 x SMD3014
- Nominal power: 18.0 W
- Power consumption during operation: 18.0 W
- Current demand: 400 mA
- Colour temperature: 3000 K
- Light colour: warm white
- Nominal luminous flux: 990-1150 Lumen
- Rated luminous flux: 1150 Lumen
- Luminous intensity: 366 Candela
- Nominal beam angle: 120°
- Rated beam angle: 120°
- Colour rendering index CRI: Ra 75
- Energy efficiency class: A
- Weighted energy consumption: 18.00 kWh / 1,000 h
- Electrical power factor: 0.90
- Comparable incandescent bulb power: 80 W

- Nominal life span: 30,000 hours
 - Rated life span: 30,000 hours
 - Switching cycles: 150,000 x
 - Remaining brightness at end of life span: 805 Lumen
 - Start-up time (to 60%): 0.02 second(s)
 - Ignition time: 0.02 second(s)
 - Luminous efficiency: 63.9 Lumen / Watt
-
- Dimensions panel (Ø / Length): 238 x 14.8 mm
 - Dimensions driver (L/W/H): 115 x 45 x 27 mm
 - Hydrargyrum (mercury) content: 0.0 mg
 - Dimmable: No
 - Protection class: IP 40
 - Operating temperature: -20 - +40 °C

Package content

- LED panel light
- Driver
- Mounting clamps

Images

